# Midterm I Review / Comments on Topics Covered and Relationships

Cryptographic Hardware for Embedded Systems ECE 3170

Fall 2025

Assoc. Prof. Vincent John Mooney III
Georgia Institute of Technology

# Reading

- The following reading has been assigned in the prior lecture notes
  - Chapters 1, 2, 3, 7, 9, 11, 12, 14 part 10 only, 17 parts 4 and 6 only, 18 and 19 of the course textbook by Schneier
  - Chapter 3 of the optional textbook by Katz and Lindell
- The following reading has been recommended for your general knowledge but is not assigned
  - NIST Special Publication 800-22 Revision 1a, "A Statistical Test Suite for Random and Pseudorandom Number Generators for Cryptographic s," Rukhin et al., April 2010, https://nvlpubs.nist.gov/nistpubs/legacy/sp/nistspecialpublication800-22r1a.pdf
- NOTE that you are responsible for everything that is explained in lecture!!!

## Notation from Schneier

- C<sub>i</sub> is ciphertext message i
- P<sub>i</sub> is plaintext message i
- *E<sub>k</sub>* is encryption with key *k* 
  - Note that *E* could be symmetric or asymmetric
  - $E_k(P_i) = C_i$
- $D_k$  is decryption with key k
  - Note that D could be symmetric or asymmetric
  - However, for asymmetric cryptographic, need distinct keys
    - $E_{k1}$  and  $D_{k2}$  where k1 is the public "key" and k2 is the private "key"
    - $E_{k1}(P_i) = C_i$
    - $D_{k2}(C_i) = P_i$
- {X} is a set of elements of type X
- | is "such that"; e.g., integer  $i \mid 3 < i < 5$  implies that i = 4

## Notation from Katz and Lindell

- {X} is a set of elements of type X
- *m* is a message in plaintext
  - m is composed of smaller blocks  $m_i$  suitable for individual encryption steps
  - $m = \{m_i\}$
- $c_i$  is ciphertext corresponding to message block  $m_i$
- c is ciphertext corresponding to message m
- Enc<sub>k</sub> is encryption with key k
  - $c \leftarrow Enc_k(m)$
- Dec<sub>k</sub> is decryption with key k
  - $m \leftarrow Dec_k(c)$
- $MAC_k$  is generation of a message authentication code t with key k
  - $t \leftarrow Mac_k(m)$  or, alternatively,  $t \leftarrow Mac_k(c)$
- <a,b> is a concatenation of a followed by b

#### Basics

- Terminology, attacks (e.g., CCA), standards
  - Cryptography I (Lecture 2)
- Birthday attack
  - Cryptography II (Lecture 3)
- Data Encryption Standard (Lecture 4)
- Asymmetric cryptography using RSA (Lecture 5)
- Number theory, complexity, Galois field (Lecture 6)
- Authentication I (Lecture 7)
  - Entity authentication
  - Message integrity
  - Nonrepudiation
  - Protocols, Man-in-the-Middle, Replay and Spoofing attacks

# First Step (Just One Step up from the Basics)

- Hash functions (Lecture 8)
  - One-way
    - Example: MD5
  - Three different types of "resistance"
    - Relationship between the three
- Encryption modes: ECB and CBC (Lecture 9)
  - Issues: initialization vector, ciphertext stealing
- Theory of cryptography using block ciphers (Lecture 10)
  - Confusion and diffusion
    - S-box and permutation
  - Feistel networks
- Message Authentication Codes and three Encryption + MAC options
  - Different ways to encrypt a message and authenticate its integrity (Lecture 11)

# Second Step up from the Basics

- Number theory, complexity, Galois field (Lecture 11)
- Digital signatures (Lecture 12)
- Advanced Authentication (Lecture 13)
- CCA attacks on some ciphers (Lecture 14)
  - Note the use of a theoretical construct called an "oracle" as well as unlimited errors
- Key length (Lecture 15)

# Third and Final Step up from the Basics

- Using a Block Cipher as a MAC (Lecture 16)
- Shift registers, feedback and hash properties (Lecture 17)
  - Maximum length sequence, primitive polynomial
  - Context: digital systems test (Lecture 18)
  - NIST tests for randomness (Lecture 19)